

PCB BOARD LAYOUT









LED Specification

Standard LED Color	LED Wavelength	Forward (V MAX)	Typical (V TYP)	Luminous Intensity
Green	560-580 nm	2.5V	2.1-2.2V	9-25 MCD
Yellow	580-610 nm	2.5V	2.1-2.2V	9-30 MCD
Orange	580-610 nm	2.5V	2.1-2.2V	50-100 MCD

1. LED intensity/wavelength measured with Photo Research PR-650 Colormeter
2. With a forward current of 20 mA,Absolute Maximum Ratings (Ta=25℃)

Comply with RoHS B TOP

Specification:

1:TOLERANCES UNLESS OTHERWISE SPECIFIED :
0~10±0.15、10~20±0.2、20~40±0.25、
40~70±0.3、≥70±0.4

2:JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS,PART 68 SUBPART F.

B-TOP® 东莞市博腾电子科技有限公司 Dongguan BroadTop Electronic Technology Co., Ltd.		Designed		MATERIAL		DESCRIPTION	B59(45-01)G8-28-1223-C12(2X1 EMI G-Y LED)		
FIRST ANGLE PROJECTION	CUSTOMER	Checked		SCALE	2:1	UNIT	mm	MODEL NO.	B01041035611	REV.	V1.0
	MODEL NO.	Approved							

SHEMATIC RV1



ELECTRICAL SPECIFICATIONS AT 25°C

Insertion Loss dB max	Return Loss dB min			Crosstalk(db TYP)			Common Mode Rejection (dB TYP)		Hipot(vrms)
1-100MHz	1-30MHz	30- 60MHz	60- 100MHz	1-30MHz	30- 60MHz	60- 100MHz	1-50MHz	50-150MHz	
-1.0	-18	-16	-12	-40	-35	-30	-30	-20	1500/0.5mA

DESCRIPTION

ELECTRICAL:
- RJ45 With internal Magnetics Connector
- Designde to support such applications as:Ethernet Equipment Complex,Switches,Routers,Firewalls,Servers and Hub
- Internal magnetics are 100% electrically tested for functionality per IEEE802.3 requirement
- RoHS peak wave solder temperature rating 235℃
- High performance for maximum EMI suppression
- 350uH minmum OCL with 8mA bias current
- PoE rating:15W,350mA,48V (For PoE Products only)

MECHANICAL:
- JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS,PART 68 SUBPART F.
- INSERTION FORCE: 2 CONTACTS----350g 4 CONTACTS----500g 6 CONTACTS----750g 8 CONTACTS----900g 10 CONTACTS----1050g
- RETENTION STRENGTH: 7.7Kgs BETWEEN JACK AND PLUG
- DURABILITY: 750 MATING CYCLES Mini

Comply with RoHS B TOP

MATERIAL:
- HOUSING: 1) GLASS FILLED PA66 (UL 94V-0) 2) GLASS FILLED PA46/LCP (UL 94V-0) 3) GLASS FILLED PBT (UL 94V-0)
- SPRING WIRE: 1) 0.2-0.45mm DIA PHOSPHOR BRONZE GOLD PLATING OVER NICKEL 2) 0.2-0.35mm THICKNESS PHOSPHOR BRONZE ALLOY SELECTIVE GOLD PLATING OVER NICKEL
- SHIELDING: 0.12-0.24mm THICKNESS COPPER ALLOY WITH TIN PLATED
- GOLD PLATING: 3μ", 6μ", 15μ", 30μ", 50μ"

WORKING TEMPERATURE: -20℃~70℃

TOLERANCES UNLESS OTHERWISE SPECIFIED : 0~10±0.15、10~20±0.2、20~40±0.25、40~70±0.3、≥70±0.4

B N (Z) G X - M - A B C D - E H I

- B: "B" with the company code
- N: Series of products: 60:Double deck RJ45 connector + transformer series(In sidelong footprint); 59:Double deck RJ45 connector + transformer series(In vertical footprint);50: Single RJ45 + transformer series;52/53/55/56 LED/56/57/59: Ordinary RJ45 series;DX: that strip line series; 40: Conversion said Connectivity 80: Series that UK; 91: Automotive connector public Block;92: Automotive connector mother Block; 93: HDMI the head;94: HDMI mother Block; 95: SMT series; 96: RHS for switches
- (Z): Family code (sequence id) :1-99
- G: Type of product code: G: Gigabit RJ45 transformer; F: 100Base RJ45 transformer; W:for no transformer RJ45 products; W: Series for board-to-board code
- X: Number of magnetic ring
- M: The No. of circuit
- A: Products luminous definition: 0 - No LED; 1 -Left Yellow Right Green; 2 - Left Green Right Yellow; 3 - Double Green; 4 - Double Yellow; 5 - LED straight for the pin; 6 - A special definition;7 - Single linear LEDs
- B: Product shielding definition: 0 - no shielding shell; 1 - without shielding shell shrapnel; 2 - shieldIng a shell shrapnel; 3 - a half-shield shell;
- C: Electroplating product definition: gold-plated terminals(degrees after nickel plated) 1-Fμ"; 2-3μ"; 3-6μ"; 4-15μ"; 5-30μ"; 6-50μ"; 7-(Ni-50μ" ,Sn-80-120μ");
- D: Pin definition of the product:F-Pin after; B-Pin back; C- No definition of the product
- E: Product definition plastic materials: 1-PA66,2-PA46, 3-PA, 4-PA6, 5-PBT, 6-ABS, 7-PA9T,8-PC
- H: Product definition LOGO: 1 - Press "B-TOP";2- No "B-TOP" ; 3- Other companies LOGO
- I: Products out port" 1-2X1" 2-2X2" 4-2X4" 5-2X5" 6-2X6" 8-2x8" A-1X1" B-1X2" C-1X4" D-1X5 " E-1X6" T-1X8" U-(USB+RJ45)" P-TAB UP1X1" H-TAB UP1X2" K-TAB UP1X4"

B-TOP® 东莞市博腾电子科技有限公司 Dongguan BroadTop Electronic Technology Co., Ltd.	Designed		MATERIAL		DESCRIPTION	BT G8-28	
	Checked						
FIRST ANGLE PROJECTION	CUSTOMER		SCALE	1.8:1	UNIT	mm	MODEL NO.	B80020002811	REV.
	MODEL NO.		Approved						